

Rugged-Reliable Two-way Radio



Support LTE(4G)

Network

- Worldwide Communication Range
- 1.8 Inch Color LCD Display
- Group Call and Individual Call
- Support REAL PTT Platform



SE650

Handheld Two-way Radio

SMART PTT

Product Features


- 1.8-inch color screen, different backlight modes optional
- Time and Date Calibration
- 2/3/4G network can be manually/automatically switched
- GPS positioning function
- Displaying the user name and group name
- Support group call, individual call
- Signal strength Indicator
- Current Battery Indicator
- Key lock/unlock function
- Support Emergency Alarm(SOS)
- Voice Code 4K/8K optional
- REAL-PTT platform

Specifications

Cat 4 Version Frequency Range	B1/B3/B5/B7/B8/B20@FDD LTE
	B38/B40/B41@TDD LTE
	B1/B5/B5@WCDMA
	B3/B8@GSM
	B1/B2/B3/B4/B5/B7/B8/B28@FDD LTE
	B40@TDD LTE
	B1/B2/B5/B8@WCDMA
	B2/B3/B5/B5@GSM
	B2/B4/B5/B12/B13/B14/B66/B71@FDD LTE
B2/B4/B5@WCDMA	
Cat 1 Version Frequency Range	B1/B3/B5/B7/B8/B20@FDD LTE
	B38/B40/B41@TDD LTE
Operating System	LINUX
GPS	Yes
SOS	Yes
Working Mode	Semi-Duplex
RX Sensitivity	LTE ≤ -96 dBm(4G)
	GSM/WCDMA ≤ -108 dBm (2G/3G) ;
RF Power	23dBm $\leq P \leq 30$ dBm
Audio Output	500mW
Working Voltage	DC3.7V
Battery Capacity	5200mAh
Dimension	52X33X102mm
Weight	Around 220g (Battery& Antenna included)
Working Temperature	-20°C - 60°C
Storage Temperature	-30°C - 80°C

Above specifications are tested according to TIA/EIA-603.
Above specifications are subject to change without any notice due to technology enhancement.

Accessories



Dual Sim Card Slot



Your Local Dealer



A Smart Communication Solution, Ahead of It's Time !